

SUBPLATES

CAST IRON

- 5000 PSI MAXIMUM PRESSURE
- IMPERIAL THREAD

PART NUMBER	CETOP	DESCRIPTION
DSGM-01Y-3090	D03	3/8" NPT BOTTOM PORT
DSGM-01R-3090		3/8" NPT SIDE PORT
DSGM-03X-2190	D05	1/2" NPT BOTTOM
DSGM-03Y-2190		3/4" NPT BOTTOM
DHGM-04X-2090	D07	3/4" NPT BOTTOM
DHGM-06-5090	D08	3/4" NPT BOTTOM
DHGM-06X-5090		1" NPT BOTTOM

ALUMINUM

- 3000 PSI MAXIMUM PRESSURE
- IMPERIAL THREAD

PART NUMBER	CETOP	DESCRIPTION
SPA03S06S	D03	SAE 06 SIDE PORT
SPA05S08S	D05	SAE 08 SIDE PORT
SBR12830	D03	SAE 08 SIDE & BOTTOM PORT WITH RELIEF CAVITY C10-2 *
SPA05S08SBT10	D05	SAE 08 SIDE & BOTTOM WITH RELIEF CAVITY T10-A *

*SELECT A RELIEF TO GO WITH THIS MODELS

MANIFOLDS

- MADE IN ALUMINUM
- 3000 PSI MAXIMUM PRESSURE
- DUCTILE IRON AVAILABLE
- CUSTOM MANIFOLD AVAILABLE ON DEMAND

CETOP D03

- P & T PORTS: SAE 10
- A & B PORTS: SAE 08
- USE RELIEF VME06-EN-3.0 IF NEEDED

CETOP D05

- P & T PORTS: SAE 12
- A & B PORTS: SAE 10
- USE RELIEF RP3A-20CL IF NEEDED



BUILD THE MODEL NUMBER YOU NEED

CIRCUIT	CETOP	NB. OF STATIONS	RELIEF OPTION
PARALLEL EAM	D03 263	1 to 8	NO RELIEF Y
SERIE EAMS	D05 265		WITH RELIEF CAVITY Z

DESCRIPTION OF YOUR NEED			
MANIFOLD	SERIE	D05	3 STATIONS WITH RELIEF CAVITY
# MODEL			
EAMS	265	3	Y

VALVES

2 WAY, 2 POSITIONS, NORMALLY CLOSE

PART NUMBER	GPM	MAX PSI	CAVITY	COIL	CIRCUIT	
PB-S2B-00	8	3500	C8-2	P		
EP08W2A05M05	10	5000		EC04W		
DE-S2B-00	15	3500	C10-2	D		
EP10W2A05M05	17.5	5000		EC04W		
TT-S2B-00	25	3000	C12-2	T		
EP12W2A05M05	37.5	5000		EC04W		
SJ-S2B-00	30	3500	C16-2	D		
EP16W2A05M05	37.5	5000		EC04W		
DE-S2I-00	4	3000	C10-2	D		
EP08W2A31M05	10	5000	C8-2	EC04W		
EP10W2A31M05	17.5	5000	C10-2			
EP16W2A631M05	37.5	5000	C16-2			



2 WAY, 2 POSITIONS, NORMALLY OPEN

PART NUMBER	GPM	MAX PSI	CAVITY	COIL	CIRCUIT	
PB-S2D-00	10	3500	C8-2	P		
EP08W2A06M05	10	5000		EC04W		
DE-S2D-00	15	3500	C10-2	D		
EP10W2A06M05	17.5	5000		EC04W		
TT-S2D-00	30	3000	C12-2	T		
EP12W2A06M05	37.5	5000		EC04W		
SJ-S2D-00	40	3000	C16-2	D		
EP16W2A06M05	37.5	5000		EC04W		
EP08W2A32M05	10	5000	C8-2	EC04W		
EP10W2A32M05	17.5	5000	C10-2			
EP16W2A632M05	37.5	5000	C16-2			



3 WAY, 2 POSITIONS

PART NUMBER	GPM	MAX PSI	CAVITY	COIL	CIRCUIT
ES08W3A11N04	2.5	3000	C8-3	EC04W	
DF-S3A-00	10	3000	C10-3	D	
TYPICALLY USED FOR SINGLE ACTING CYLINDER					
DF-S3B-00	8	3000	C10-3	D	
TYPICALLY USED AS A SELECTOR					

4 WAY, 2 POSITIONS

PART NUMBER	GPM	MAX PSI	CAVITY	COIL	CIRCUIT
ES08W4A10N04	3	3000	C8-4	EC04W	
DG-S4A-00	10		C10-4	D	
ES08W4A11N04	4	3000	C8-4	EC04W	
DG-S4B-00	10		C10-4	D	

