

V20 MANUAL VALVES

SECTIONAL V20 VALVE

- 20 GPM MAX
- 3500 PSI MAX PRESSURE
- INTERCHANGEABLE WITH GRESEN V20
- LOAD SENSING AND ELECTRIC VERSIONS ARE AVAILABLE



POPULAR PARTS

| PART NUMBER | DESCRIPTION   |
|-------------|---|
| 20I2E       | INLET SAE 12 WITH RELIEF 2200-3000 PSI                        |
| 20P1AA1AA   | WORK SECTION SAE 12, SINGLE ACTING, SPRING RETURN, STD HANDLE |
| 20P1BA1AA   | WORK SECTION SAE 12, DOUBLE ACTING, SPRING RETURN, STD HANDLE |
| 20P1BE1AA   | WORK SECTION SAE 12, DOUBLE ACTING C/W PNEUMATIC ACTUATOR     |
| 20P1AE1AA   | WORK SECTION SAE 12, SINGLE ACTING C/W PNEUMATIC ACTUATOR     |
| 20P1DD1AA   | WORK SECTION SAE 12, DOUBLE ACTING C/W 4TH FLOAT POSITION     |
| 20E22       | OUTLET SAE 12   |
| 66040200-X  | TIE-ROD (SPECIFY NUMBER OF SECTION "X")                       |
| 660290004   | POWER BEYOND  |
| 660190007   | STANDARD HANDLE   |
| 660190004   | 3 POSITION DETENT   |
| 660290401   | PORT RELIEF 500-1350 PSI                                      |
| 660290403   | PORT RELIEF 1350-1750 PSI                                     |
| 660290405   | PORT RELIEF 1750-2200 PSI                                     |
| 660290407   | PORT RELIEF 2200-3000 PSI                                     |

NUMBER OF WORK SECTIONS

|   | 1    | 2    | 3    | 4     | 5     | 6     | 7     | 8     |
|---|------|------|------|-------|-------|-------|-------|-------|
| A | 2.50 | 4.25 | 6.00 | 7.75  | 9.50  | 11.25 | 13.00 | 14.75 |
| B | 4.88 | 6.63 | 8.38 | 10.13 | 11.88 | 13.63 | 15.38 | 17.13 |

