


PRESSURE CONTROL

FUNCTION	PART NUMBER	MAX GPM	MAX PSI	PSI RANGE	CAVITY	SCHEMATIC
VENTED RELIEF	RV11A30AL	15	5000	100 - 3000	T11-A	
	RV2A30AL	30			T2-A	
	RV17A30AL	60			T-17A	
	RV19A30AL	120			T-19A	
PRESSURE REDUCING	PB11A30AL	10	5000	100 - 3000	T11-A	
	PB2A30AL	20			T2-A	
	PB17A30AL	40			T-17A	
	PB19A30AL	80			T-19A	
PRESSURE REDUCING/RELIEVING	DF-PRP-00-3000	10	3000	100 - 3000	C10-3	
	SK-PRP-00-3000	20		500 - 3000	C16-3	
	PP11A30AL	10	5000	100 - 3000	T11-A	
	PP2A30AL	20			T2-A	
	PP17A30AL	40			T-17A	
	PP19A30AL	80			T-19A	
SEQUENCE	SP11A30AL	15	5000	100 - 3000	T11-A	
	SP2A30AL	30			T2-A	
	SP17A30AL	60			T-17A	
	SP19A30AL	120			T-19A	
UNLOADING	DF-PWE-00-0425	10	3000	50-425	C10-3	
	DF-PWE-00-1500			425-1500		



LINE MOUNT BODIES

- 3000 PSI MAXIMUM PRESSURE
- DUCTILE IRON AVAILABLE ON DEMAND

PART NUMBER	CAVITY	PORTS 1 & 2	PORT 3	DIMENSIONS						HOLES (2)
				A	B	C	D	E	F	
30102354	C10-3	SAE 08	SAE 08	2.5	2.5	1.5	2.25	0.38	0.28	-
30102576	C16-3	SAE 12	SAE 12	4.0	4.0	2.0	3.38	0.88	-	0.38
11A-S-90-S-8	T-11A	SAE 08	SAE 06	3.0	2.75	1.26	2.09	0.38	0.44	0.34
2A-S-90-S-12	T-2A	SAE 12	SAE 06	3.25	3.0	1.5	2.25	0.5	0.5	0.42
17A-S-90-S-16	T-17A	SAE 16	SAE 06	4.25	4.0	2.36	2.75	0.75	0.75	-
19A-S-90-S-20	T-19A	SAE 20	SAE 06	5.0	5.0	3.0	4.0	0.5	0.5	-

