


## TPV 1000

### VARIABLE DISPLACEMENT CLOSED LOOP SYSTEM AXIAL PISTON PUMPS



**FEATURES:**

- HIGH ROTATION SPEED
- COMPACT DESIGN
- SUITABLE FOR MULTIPLE PUMP ASSEMBLY


**ACCESSORIES:**

- BY-PASS VALVE
- CONTROL LEVER WITH OR WITHOUT RETURN SPRING
- HYDRAULIC SERVO-CONTROL
- ELECTRO-PROPORTIONAL SERVO-CONTROL
- PURGE VALVE
- SAE-A OR SAE-B (ONLY SERVO) MOUNTING
- SCREW BY-PASS

DISPLACEMENT IN <sup>3</sup> (CM <sup>3</sup> ) / REV.	RATED PRESSURE PSI	PEAK PRESSURE PSI	MAXIMUM RPM	WEIGHT KG (LB)
6 (0.37)	3045	4350	3600	8,8 (19)
0.49 (8)				
0.55 (9)				
0.67 (11)				
0.73 (12)				
0.79 (13)				
0.9 (15)				
1.0 (17)				
1.1 (18)	2900	3625	3200	
1.2 (19)				
1.3 (21)				

## TPV 1200

### VARIABLE DISPLACEMENT CLOSED LOOP SYSTEM AXIAL PISTON PUMPS



**FEATURES:**

- LOW NOISE LEVEL
- HIGH ROTATION SPEED
- COMPACT DESIGN AND REDUCED LENGTH
- SUITABLE FOR MULTIPLE PUMP ASSEMBLY

**ACCESSORIES:**

- AUXILIARY GEAR PUMPS GROUP 1-2
- CONTROL LEVER WITH OR WITHOUT RETURN SPRING
- HYDRAULIC SERVO-CONTROL
- ELECTRO-PROPORTIONAL SERVO-CONTROL
- MAN ON BOARD
- PURGE VALVE
- SAE-A OR SAE-B (ONLY SERVO) MOUNTING
- SCREW BY-PASS

DISPLACEMENT IN <sup>3</sup> (CM <sup>3</sup> ) / REV.	RATED PRESSURE PSI	PEAK PRESSURE PSI	MAXIMUM RPM	WEIGHT KG (LB)
0.37 (6)	3045	4350	3600	19 (42)
0.49 (8)				
0.55 (9)				
0.67 (11)				
0.73 (12)				
0.79 (13)				
0.9 (15)				
1.0 (17)				
1.1 (18)	2900	3625	3200	
1.2 (19)				
1.3 (21)				