



TPVTC 1500

VARIABLE DISPLACEMENT CLOSED LOOP SYSTEM AXIAL PISTON PUMPS



FEATURES:

- LOW NOISE LEVEL
- HIGH ROTATION SPEED
- HIGH POWER DENSITY
- COMPACT DESIGN
- SUITABLE FOR MULTIPLE PUMP ASSEMBLY
- BUILT-IN PRESSURE RELIEF VALVES


ACCESSORIES:

- AUXILIARY GEAR PUMPS GROUP 2 SAE-A
- HYDRAULIC SERVO-CONTROL
- HYDRAULIC SERVO-CONTROL WITH FEED BACK
- ELECTRO-PROPORTIONAL SERVO-CONTROL
- ELECTRO-PROPORTIONAL SERVO-CONTROL WITH FEED BACK
- MANUAL LEVER SERVO-CONTROL WITH FEED BACK
- MAN ON BOARD
- PURGE VALVE
- SAE-B MOUNTING
- SCREW BY-PASS
- SENSORS AND TRANSDUCERS AVAILABLE ON REQUEST

DISPLACEMENT IN ³ (CM ³) / REV.	RATED PRESSURE PSI	PEAK PRESSURE PSI	MAXIMUM RPM	WEIGHT KG (LB)
1.0 (17)	5075	5800	3600	14 (31)
1.1 (18)				
1.2 (19)				
1.3 (21)				

TPV 3200

VARIABLE DISPLACEMENT CLOSED LOOP SYSTEM AXIAL PISTON PUMPS



FEATURES:

- HIGH ROTATION SPEED
- COMPACT DESIGN
- SUITABLE FOR MULTIPLE PUMP ASSEMBLY

ACCESSORIES:

- MANUAL DISPLACEMENT SERVO-CONTROL
- HYDRAULIC PROPORTIONAL SERVO-CONTROL
- ELECTRO-PROPORTIONAL SERVO-CONTROL
- AUTOMOTIVE
- SPECIAL VERSIONS
- SAE-B MOUNTING

DISPLACEMENT IN ³ (CM ³) / REV.	RATED PRESSURE PSI	PEAK PRESSURE PSI	MAXIMUM RPM	WEIGHT KG (LB)
1.3 (21)	3625	5075	3600	22 (48)
1.7 (28)				