


TPV 3600

VARIABLE DISPLACEMENT CLOSED LOOP SYSTEM AXIAL PISTON PUMPS



FEATURES:

- LOW NOISE LEVEL
- HIGH ROTATION SPEED
- HIGH POWER DENSITY
- COMPACT DESIGN
- SUITABLE FOR MULTIPLE PUMP ASSEMBLY
- BUILT-IN PRESSURE RELIEF VALVES


ACCESSORIES:

- AUXILIARY GEAR PUMPS GROUP 2 SAE-A AND GROUP 3 SAE-B
- HYDRAULIC SERVO-CONTROL
- HYDRAULIC SERVO-CONTROL WITH FEED BACK
- ELECTRO-PROPORTIONAL SERVO-CONTROL
- ELECTRO-PROPORTIONAL SERVO-CONTROL WITH FEED BACK
- MANUAL LEVER SERVO-CONTROL WITH FEED BACK
- MAN ON BOARD
- PURGE VALVE
- SAE-B MOUNTING
- SCREW BY-PASS
- PRESSURE CUT-OFF
- SENSORS AND TRANSDUCERS AVAILABLE ON REQUEST

DISPLACEMENT IN ³ (CM ³) / REV.	RATED PRESSURE PSI	PEAK PRESSURE PSI	MAXIMUM RPM	WEIGHT KG (LB)
1.6 (26)	5075	6525	3600	28 (62)
1.7 (28)				
1.8 (30)				
1.9 (31)				
2.0 (32)				
2.1 (34)				
2.2 (36)				
2.3 (38)				

TPV 4300

VARIABLE DISPLACEMENT CLOSED LOOP SYSTEM AXIAL PISTON PUMPS



FEATURES:

- HIGH ROTATION SPEED
- COMPACT DESIGN
- SUITABLE FOR MULTIPLE PUMP ASSEMBLY
- BUILT-IN PRESSURE RELIEF VALVES

ACCESSORIES:

- HYDRAULIC SERVO-CONTROL
- ELECTRO-PROPORTIONAL SERVO-CONTROL
- SAE-B MOUNTING
- MAN ON BOARD
- SCREW BY-PASS
- SPECIAL VERSIONS

DISPLACEMENT IN ³ (CM ³) / REV.	RATED PRESSURE PSI	PEAK PRESSURE PSI	MAXIMUM RPM	WEIGHT KG (LB)
2.0 (32)	3625	5057	3600	23 (51)
2.3 (38)				
2.7 (45)				
3.1 (50)				