


TPV 5000

VARIABLE DISPLACEMENT CLOSED LOOP SYSTEM AXIAL PISTON PUMPS



FEATURES:

- HIGH ROTATION SPEED
- COMPACT DESIGN
- SUITABLE FOR MULTIPLE PUMP ASSEMBLY


ACCESSORIES:

- MANUAL DISPLACEMENT SERVO-CONTROL
- HYDRAULIC PROPORTIONAL SERVO-CONTROL
- ELECTRO-PROPORTIONAL SERVO-CONTROL
- AUTOMOTIVE
- SPECIAL VERSIONS
- SAE-B MOUNTING

DISPLACEMENT IN ³ (CM ³) / REV.	RATED PRESSURE PSI	PEAK PRESSURE PSI	MAXIMUM RPM	WEIGHT KG (LB)
2.8 (46)	4350	5800	3600	29 (64)
3.1 (50)				
3.9 (64)				

TPV 9000

VARIABLE DISPLACEMENT CLOSED LOOP SYSTEM AXIAL PISTON PUMPS



FEATURES:

- HIGH ROTATION SPEED
- HIGH PRESSURE
- HIGH PERFORMANCES
- COMPACT DESIGN

ACCESSORIES:

- MANUAL DISPLACEMENT SERVO-CONTROL
- HYDRAULIC PROPORTIONAL SERVO-CONTROL
- ELECTRO-PROPORTIONAL SERVO-CONTROL
- SAE-C MOUNTING

DISPLACEMENT IN ³ (CM ³) / REV.	RATED PRESSURE PSI	PEAK PRESSURE PSI	MAXIMUM RPM	WEIGHT KG (LB)
3.4 (55)	5800	6525	4000	55 (121)
72 (4.4)			4100	68 (150)
90 (5.5)			4000	
110 (6.7)			3800	