



PART NUMBER	CYLINDER BORE	OUTSIDE DIAMETER	ROD DIAMETER	*A	B	C	D	*E	F	G	H	I	J	K	PORTS*
CL15-XX-S	1.50"	1.875"	1.00"	8.25"	1.62"	0.87"	1.37"	2.25"	1.37"	1.50"	0.76"	-	0.93"	1.87"	SAE 4
CL20-XX-S	2.00"	2.375"	1.25"	10.25"	2.12"	1.12"	2.12"	3.12"	2.12"	2.00"	1.01"	-	1.00"	2.06"	SAE6
CL25-XX-S	2.50"	2.875"	1.50"	10.25"	2.12"	1.12"	2.12"	3.12"	2.12"	2.00"	1.01"	-	0.81"	2.18"	SAE 8
CL30-XX-S	3.00"	3.50"	1.50"	10.25"	2.12"	1.12"	2.12"	3.12"	2.12"	2.00"	1.01"	-	0.81"	2.18"	SAE 8
CL35-XX-S	3.50"	4.00"	1.75"	10.25"	2.37"	1.12"	2.00"	3.12"	2.12"	2.00"	1.01"	2.12"	0.93"	2.18"	SAE 8
CL40-XX-S	4.00"	4.50"	2.00"	10.25"	2.37"	1.12"	1.75"	3.12"	2.00"	2.00"	1.01"	2.00"	1.06"	2.18"	SAE 8
CL50-XX-S	5.00"	5.50"	2.50"	13.00"	3.12"	1.62"	2.25"	3.62"	2.25"	3.00"	1.51"	-	1.37"	2.75"	SAE 12

- 1. FOR 8" STROKE : A = 12.25" (2" TO 4" BORE)
- 2. FOR 8" STROKE : E = 5.12" (2" TO 4" BORE)

MAXIMUM RETRACTED WORKING PRESSURE : 3000 psi
 MAXIMUM EXTENDED WORKING PRESSURE : SEE TABLE
 RETRACTED AND STROKE TOLERANCE ± 1/8"

* NPT PORTS ARE ALSO AVAILABLE FROM 1.5" TO 4" BORE CYLINDERS

WELDED FEMALE CLEVIS TYPE									
PART NUMBER	BORE & STROKE	DIMENSIONS		ROD DIAMETER	PIN SIZE	PORTS*	COLUMN LOADS (LBS)	PRESSURE (PSI)	WEIGHT (LBS)
		RETRACTED	EXTENDED						
CL1504-S	1.5" X 4"	12-1/4"	16-1/4"	1"	3/4"	SAE 4	5300	3000	8
CL1506-S	1.5" X 6"	14-1/4"	20-1/4"				5300	3000	9
CL1508-S	1.5" X 8"	16-1/4"	24-1/4"				5300	3000	11
CL1510-S	1.5" X 10"	18-1/4"	28-1/4"				5300	3000	12
CL1512-S	1.5" X 12"	20-1/4"	32-1/4"				5300	3000	13
CL1514-S	1.5" X 14"	22-1/4"	36-1/4"				5300	3000	14
CL1516-S	1.5" X 16"	24-1/4"	40-1/4"				5300	3000	15
CL1518-S	1.5" X 18"	26-1/4"	44-1/4"				4800	2700	17
CL1520-S	1.5" X 20"	28-1/4"	48-1/4"				4000	2200	18
CL1524-S	1.5" X 24"	32-1/4"	56-1/4"				2900	1600	20

* NPT PORTS ARE ALSO AVAILABLE.
 NOTE : COLUMN LOAD IS THE MAXIMUM PUSHING LOAD SUGGESTED USING A MINIMUM SAFETY FACTOR OF 2 AND BASED ON A PIN TO PIN MOUNTING CALCULATION.



WELDED FEMALE CLEVIS TYPE												
PART NUMBER	BORE & STROKE	DIMENSIONS		ROD DIAMETER	PIN SIZE	PORTS*	COLUMN LOADS (LBS)	PRESSURE (PSI)	WEIGHT (LBS)			
		RETRACTED	EXTENDED									
CL2004-S	2" X 4"	14-1/4"	18-1/4"	1-1/4"	1"	SAE 6	9400	3000	14			
CL2006-S	2" X 6"	16-1/4"	22-1/4"				9400	3000	16			
CL2008-S	2" X 8"	20-1/4"	28-1/4"				9400	3000	18			
CL2010-S	2" X 10"	20-1/4"	30-1/4"				9400	3000	19			
CL2012-S	2" X 12"	22-1/4"	34-1/4"				9400	3000	21			
CL2014-S	2" X 14"	24-1/4"	38-1/4"				9400	3000	23			
CL2016-S	2" X 16"	26-1/4"	42-1/4"				9400	3000	25			
CL2018-S	2" X 18"	28-1/4"	46-1/4"				9400	3000	26			
CL2020-S	2" X 20"	30-1/4"	50-1/4"				9100	2900	28			
CL2024-S	2" X 24"	34-1/4"	58-1/4"				6700	2100	31			
CL2028-S	2" X 28"	38-1/4"	66-1/4"				5200	1600	35			
CL2030-S	2" X 30"	40-1/4"	70-1/4"				4600	1400	36			
CL2032-S	2" X 32"	42-1/4"	74-1/4"				4100	1300	38			
CL2034-S	2" X 34"	44-1/4"	78-1/4"				3700	1100	40			
CL2036-S	2" X 36"	46-1/4"	82-1/4"				3400	1000	42			
CL2040-S	2" X 40"	50-1/4"	90-1/4"				2800	800	45			
CL2048-S	2" X 48"	58-1/4"	106-1/4"				2000	600	52			
CL2504-S	2.5" X 4"	14-1/4"	18-1/4"				1-1/2"	1"	SAE 8	14700	3000	18
CL2506-S	2.5" X 6"	16-1/4"	22-1/4"							14700	3000	20
CL2508-S	2.5" X 8"	20-1/4"	28-1/4"							14700	3000	24
CL2510-S	2.5" X 10"	20-1/4"	30-1/4"	14700	3000	25						
CL2512-S	2.5" X 12"	22-1/4"	34-1/4"	14700	3000	27						
CL2514-S	2.5" X 14"	24-1/4"	38-1/4"	14700	3000	29						
CL2516-S	2.5" X 16"	26-1/4"	42-1/4"	14700	3000	32						
CL2518-S	2.5" X 18"	28-1/4"	46-1/4"	14700	3000	34						
CL2520-S	2.5" X 20"	30-1/4"	50-1/4"	14700	3000	36						
CL2524-S	2.5" X 24"	34-1/4"	58-1/4"	14000	2800	40						
CL2528-S	2.5" X 28"	38-1/4"	66-1/4"	10800	2200	45						
CL2530-S	2.5" X 30"	40-1/4"	70-1/4"	9600	1900	47						
CL2532-S	2.5" X 32"	42-1/4"	74-1/4"	8600	1700	49						
CL2534-S	2.5" X 34"	44-1/4"	78-1/4"	7700	1500	52						
CL2536-S	2.5" X 36"	46-1/4"	82-1/4"	7000	1400	54						
CL2540-S	2.5" X 40"	50-1/4"	90-1/4"	5800	1100	58						
CL2548-S	2.5" X 48"	58-1/4"	106-1/4"	4200	800	67						

HYDRO CUSTOM IS NOT RESPONSIBLE FOR INCORRECT RESULTS OBTAINED WITH FIGURES IN THIS DOCUMENT. INFORMATION IS FOR REFERENCE ONLY. NO OTHER CONDITIONS ARE EXPRESSED OR IMPLIED.



WELDED FEMALE CLEVIS TYPE									
PART NUMBER	BORE & STROKE	DIMENSIONS		ROD DIAMETER	PIN SIZE	PORTS*	COLUMN LOADS (LBS)	PRESSURE (PSI)	WEIGHT (LBS)
		RETRACTED	EXTENDED						
CL3004-S	3" X 4"	14-1/4"	18-1/4"	1-1/2"	1"	SAE 8	21200	3000	22
CL3006-S	3" X 6"	16-1/4"	22-1/4"				21200	3000	24
CL3008-S	3" X 8"	20-1/4"	28-1/4"				21200	3000	27
CL3010-S	3" X 10"	20-1/4"	30-1/4"				21200	3000	29
CL3012-S	3" X 12"	22-1/4"	34-1/4"				21200	3000	31
CL3014-S	3" X 14"	24-1/4"	38-1/4"				21200	3000	34
CL3016-S	3" X 16"	26-1/4"	42-1/4"				21200	3000	36
CL3018-S	3" X 18"	28-1/4"	46-1/4"				21200	3000	39
CL3020-S	3" X 20"	30-1/4"	50-1/4"				18800	2600	41
CL3024-S	3" X 24"	34-1/4"	58-1/4"				14000	1900	46
CL3028-S	3" X 28"	38-1/4"	66-1/4"				10800	1500	51
CL3030-S	3" X 30"	40-1/4"	70-1/4"				9600	1300	53
CL3032-S	3" X 32"	42-1/4"	74-1/4"				8600	1200	56
CL3034-S	3" X 34"	44-1/4"	78-1/4"				7700	1100	58
CL3036-S	3" X 36"	46-1/4"	82-1/4"				7000	900	61
CL3504-S	3.5" X 4"	14-1/4"	18-1/4"				1-3/4"	1"	SAE 8
CL3506-S	3.5" X 6"	16-1/4"	22-1/4"	28800	3000	30			
CL3508-S	3.5" X 8"	20-1/4"	28-1/4"	28800	3000	35			
CL3510-S	3.5" X 10"	20-1/4"	30-1/4"	28800	3000	36			
CL3512-S	3.5" X 12"	22-1/4"	34-1/4"	28800	3000	39			
CL3514-S	3.5" X 14"	24-1/4"	38-1/4"	28800	3000	42			
CL3516-S	3.5" X 16"	26-1/4"	42-1/4"	28800	3000	46			
CL3518-S	3.5" X 18"	28-1/4"	46-1/4"	28800	3000	49			
CL3520-S	3.5" X 20"	30-1/4"	50-1/4"	28800	3000	52			
CL3524-S	3.5" X 24"	34-1/4"	58-1/4"	26000	2700	58			
CL3528-S	3.5" X 28"	38-1/4"	66-1/4"	20100	2000	64			
CL3530-S	3.5" X 30"	40-1/4"	70-1/4"	17900	1800	67			
CL3532-S	3.5" X 32"	42-1/4"	74-1/4"	16000	1600	70			
CL3534-S	3.5" X 34"	44-1/4"	78-1/4"	14400	1500	73			
CL3536-S	3.5" X 36"	46-1/4"	82-1/4"	13000	1300	76			
CL4004-S	4" X 4"	14-1/4"	18-1/4"	2"	1"	SAE 8			
CL4006-S	4" X 6"	16-1/4"	22-1/4"				37600	3000	37
CL4008-S	4" X 8"	20-1/4"	28-1/4"				37600	3000	42
CL4010-S	4" X 10"	20-1/4"	30-1/4"				37600	3000	44
CL4012-S	4" X 12"	22-1/4"	34-1/4"				37600	3000	48
CL4014-S	4" X 14"	24-1/4"	38-1/4"				37600	3000	52
CL4016-S	4" X 16"	26-1/4"	42-1/4"				37600	3000	55
CL4018-S	4" X 18"	28-1/4"	46-1/4"				37600	3000	59
CL4020-S	4" X 20"	30-1/4"	50-1/4"				37600	3000	63
CL4024-S	4" X 24"	34-1/4"	58-1/4"				37600	3000	70
CL4028-S	4" X 28"	38-1/4"	66-1/4"				34300	2700	77
CL4030-S	4" X 30"	40-1/4"	70-1/4"				30500	2400	81
CL4032-S	4" X 32"	42-1/4"	74-1/4"				27300	2100	85
CL4034-S	4" X 34"	44-1/4"	78-1/4"				24600	1900	89
CL4036-S	4" X 36"	46-1/4"	82-1/4"				22200	1700	92

HYDRO CUSTOM IS NOT RESPONSIBLE FOR INCORRECT RESULTS OBTAINED WITH FIGURES IN THIS DOCUMENT. INFORMATION IS FOR REFERENCE ONLY. NO OTHER CONDITIONS ARE EXPRESSED OR IMPLIED.